

Example



We offer **EasyRigging PBO** integrated continuous rigging (IRC) for your 6.5 Proto

Cable	Cable	Wire	Cable	ER-Cable	Stretch	Breaking	ER- Cable	Cable	Total
Quantity	type	Size	Length	Type	mm/mm/1000kg	load kg.	Diameter	Weight gr.	Weight gr.
2	V1 / D3	3mm	10710mm	ER-W3	0.0106	1200	3mm	140	280
2	V1/D2	4mm	9860mm	ER-W4	0.0081	1550	3.5mm	187	374
2	D1	4mm	5250mm	ER-W4	0.0081	1550	3.5mm	100	200
1	Head stay	5mm	9760mm	ER-W5	0.0051	2800	4mm	235	235
2	TM Back Stay	4mm	10700mm	ER-W4	0.0081	1550	3.5mm	200	400
2	Back stay	4mm	9250mm	ER-W4	0.0081	1550	3.5mm	175	350
2	V1	5mm	Calibrated	Turnbuckles		1630		200	400
2	D1	4mm	Calibrated	Turnbuckles		2250		120	240
All standing rigging is covered by Heavy Duty braided black chafe protection cover									

Total weight 2479

V1 is a combination from D3 (Wire 3mm) and D2 (Wire 4mm) in total that makes for V1 wire 5mm diam approximate: 4.5 mm and has a stretch from : 0.0051 mm/mm/1000kg. And a breaking load from 2800 kg.

The complete set V's and D's in EasyRigging in ICR is 70% lighter then wire rigging and has 40% less stretch.!!!

We offer a total warranty of 1 year.

Weights and sizes are subject to changes.

Delivery time 2 till 3 weeks after order conformation.

€3750,- inc VAT

If you have different requirements , please do not hesitate to ask for a quote !!